

Millflo™ ANS

NR/SBR lined Fire Hoses, Single Jackets
Designed for water discharge, washdown etc. ...



Millflo ANS is also called mill discharge hose or fire hose. It is designed for water discharge, washdown etc.

Millflo ANS is a polyester single-jacket hose with a Natural rubber (NR) and SBR compound lining. Polyester jacket is 100% mildew resistant.

Millflo ANS hoses are economic hose solutions for water transfer.

Application: Suitable for construction, water discharge, washdown etc.

Inner tube: NR/SBR rubber compound lining
Jacket: Single jacket, circular woven polyester jacket, plain weave, warp yarn is made of spun polyester yarn, strips available per request

Operating Temperature Range: -22° to 158°F (-30° to 70°C) based on water

Standard Color: White (no coating), other colors (coated with Durablux™) available per request.

Standard Length: 50ft, 100ft; other lengths available per request;

Couplings: Aluminum or Brass NH/NST couplings, Camlock, and pinplug couplings etc.

Standards: Asoe corporate standard

Thin wall rubber or thin jackets available upon request for additional savings.

Recommended for:

-
- Water Discharge Solutions
- Other

Millflo™ ANS

ID		Working Pressure PSI/bar	Bursting Pressure PSI/bar
Inch	mm		
1 1/2"	39+1.5	150/10	450/30
2"	51+1.5	150/10	450/30
2 1/2"	64+1.5	150/10	450/30
3"	78+2.0	150/10	450/30
4"	104+2.0	150/10	450/30